



13 janvier 2009

Java EE 6

Ce qui vous attends

Antonio Goncalves

Architecte

Freelance



www.parisjug.org

Copyright © 2008 ParisJug. Licence CC – Creative Commons 2.0 France – Paternité – Pas d'Utilisation Commerciale – Partage des Conditions Initiales à l'Identique



« EJBs are dead... »


Rod Johnson

« Long live EJBs ! »


Antonio Goncalves

Antonio Goncalves

- Software Architect
- Former BEA Consultant
 - Experience with Application Servers
- Java EE 5 author
 - EJB3, JPA, JSF, JSP, JAX-WS...
- JCP Expert Member
 - Java EE 6, EJB 3.1, JPA 2.0
- Co-creator, co-leader of the Paris JUG




Agenda




Disclaimer

- Still under work
 - Specifications and APIs might change
 - Q2 2009 (May/June)
- Assumes you know Java EE 5

Java EE 6



A Bit of history



Richer, Easier, Lighter

- Richer
 - New specifications
- Easier
 - POJO model
 - Less XML...
 - ... even on the web tier
- Lighter
 - EJB Lite
 - Profiles and Pruning

Richer : ~28 specifications

Web Services

JAX-RPC	1.1
JAX-WS	2.2
JAXM	1.0
JAX-RS	1.1
JAXR	1.1
StAX	1.0
Web Services	1.2
Web Services Metadata	1.1

Enterprise

EJB	3.1
JAF	1.1
JavaMail	1.4
JCA	1.6
JMS	1.1
JPA	2.0
JTA	1.1

Web

JSF	2.0
JSP	2.2
JSTL	1.2
Servlet	3.0
Expression Language	1.2

Management, Security and other

Web Beans	1.0
JACC	1.1
Common Annotations	1.0
Java EE Application Deployment	1.2
Java EE Management	1.1
Java Authentication Service Provider Interface for Containers	1.0
Debugging Support for Other Languages	1.0
Bean Validation	1.0

+ Java SE 6

JAXB	2.2
JDBC	4.0
JNDI	1.5
RMI	
JMX	
JAAS	
JAXP...	


Lighter : EJB Light

- Subset of the EJB 3.1 API
- To be used in Web profile

Local Session Bean
Injection
CMT / BMT
Interceptors
Security

~~Message Driven Beans
EJB Web Service Endpoint
RMI/IIOP Interoperability
Remote interface
EJB 2.x
Timer service
CMP / BMP~~

Lighter : Profiles



Lighter : Web Profile

- Subset of full platform
- Focuses on web development
- Separate specification
- Others will come
 - Minimal (Servlet/JSP)
 - Portal....


Servlet	3.0
JSP	2.2
EL	1.2
JSTL	1.2
EJB Lite	3.1
JTA	1.1
JPA	2.0
JSF	2.0
Web Beans	1.0
JAX-RS	1.1

« ...you'll see gradual move toward the Web profile » - Rod Johnson

Pruning : Soon less specs

- Makes some specifications optional in next version
- Pruned in Java EE 6
 - Entity CMP 2.x
 - JAX-RPC
 - JAX-R
 - JSR 88 (Java EE Application Deployment)
- Stronger than @Deprecated
- Will disappear in Java EE 7
- Easier for future containers

Servlet 3.0



Ease of development

- Annotations based programming model
 - @WebServlet
 - @ServletFilter
 - @WebServletContextListener
- Deployment descriptors optional (web.xml)
 - Modular

Ease of development

```
public class MyServlet extends HttpServlet {  
    public void doGet (HttpServletRequest req,  
                      HttpServletResponse res) {  
        ....  
    }  
}
```

Deployment descriptor (web.xml)

```
<web-app>  
  <servlet>  
    <servlet-name>MyServlet</servlet-name>  
    <servlet-class>samples.MyServlet</servlet-class>  
  </servlet>  
  
  <servlet-mapping>  
    <servlet-name>MyServlet</servlet-name>  
    <url-pattern>/MyApp</url-pattern>  
  </servlet-mapping>  
  ...  
</web-app>
```


Ease of development

```
@WebServlet (urlMappings={ "/MyApp" })
public class MyServlet extends HttpServlet {

    public void doGet (HttpServletRequest req,
                      HttpServletResponse res) {
        . . . .
    }
}
```

web.xml is optional

- Same for filters and listeners

Extensibility

- Fragments *or modular* web.xml
 - Logical partitioning of a web application
- Annotations and web fragments are merged

<web-fragment>

```
<servlet>
```

```
  <servlet-name>myservlet</servlet-name>
```

```
  <servlet-class>samples.MyServlet</servlet-class>
```

```
</servlet>
```

```
<listener>
```

```
  <listener-class>samples.MyListener</listener-class>
```


```
</listener>
```

</web-fragment>

Asynchronous support

- Servlets have to wait for a response from :
 - Web service
 - JDBC connection
 - JMS message....
- *Comet* style of programming
- `@WebServlet (asyncSupported = true)`
- New APIs to `ServletRequest / ServletResponse`
 - Suspending, resuming, querying the status of the request

JSF 2.0



Ease of development

- Annotations
 - @ManagedBean
- faces-config.xml optional
- Templating based on Facelet
- Ajax Support
- Easier way of Component Development

Ease of development

```
public class DatabaseUtil {  
  
    private Cities cities;  
    ...  
}
```

faces-config.xml

```
<managed-bean>  
    <managed-bean-name>dbUtil</managed-bean-name>  
    <managed-bean-class>server.DatabaseUtil</managed-bean-class>  
    <managed-bean-scope>request</managed-bean-scope>  
    <managed-property>  
        <property-name>cities</property-name>  
        <value>#{cities}</value>  
    </managed-property>  
</managed-bean>
```


Ease of development

```
@ManagedBean (name="dbUtil", scope="request")
public class DatabaseUtil {

    @ManagedProperty (value="#{cities}")
    private Cities cities;
}
```

faces-config.xml is optional

EJB 3.1



Easier & Richer

- Optional Local Interfaces
- Singleton
- Asynchronous calls
- Cron-based Timer Service
- Packaging in a war
- Portable JNDI name
- Embeddable Container
- EJB Lite

Optional Local Interface

- @Local, @Remote
- Interfaces are not always needed
 - Only for local interfaces
 - Remote interfaces are not optional !

@Stateless

```
public class HelloBean {  
  
    public String sayHello() {  
        return "Hello Open Source";  
    }  
}
```

Singleton

- New component
 - Looks like a stateless / stateful
 - No/local/remote interface
- Follows the Singleton pattern
 - One single EJB per application per JVM
- Use to share state in the entire application
 - State not preserved after container shutdown
- Added concurrency management
 - `@ConcurrencyManagement`

Singleton

@Singleton

```
public class CachingBean {  
  
    private Map cache;  
  
    @PostConstruct void init() {  
        cache = ...;  
    }  
  
    public Map getCache() {  
        return cache;  
    }  
  
    public void addToCache(Object key, Object val) {  
        cache.put(key, val);  
    }  
}
```

Asynchronous calls

- How to have asynchronous call in EJBs ?
- JMS is to send messages not to do asynchronous calls
- Threads are not allowed (don't integrate well)
- `@Asynchronous`
- Method returns `void` or `Future<T>`
 - `java.util.concurrent` package

Asynchronous calls

```
@Stateless
public class OrderBean {

    public void createOrder() {
        Order order = persistOrder();
        sendEmail(order) ;
    }

    public Order persistOrder() {...}

    @Asynchronous
    public void sendEmail(Order order) {...}
}
```

Packaging in a war

foo.ear

lib/foo_common.jar

com/acme/**Foo**.class

foo_web.war


WEB-INF/web.xml

WEB-INF/classes

com/acme/**FooServlet**.class

foo_ejb.jar

com/acme/**FooEJB**.class



foo.war

WEB-INF/classes

com/acme/**Foo**.class

com/acme/**FooServlet**.class

com/acme/**FooEJB**.class

Portable JNDI Name

- Client inside a container (use DI)

```
@EJB Hello h;
```

- Client outside a container

```
Context ctx = new InitialContext();  
Hello h = (Hello) ctx.lookup(???) ;
```


- Portable JNDI name is specified

```
java:global/env/foo/HelloEJB
```

```
java:global/(app)/(module)/(bean)#(intf)
```


Embeddable Container

- API allowing to :
 - Initialize a container
 - Get container context
 - ...
- Can run in any Java SE environment
 - Batch processing
 - Simplifies testing
 - Just a jar file in your classpath



Embeddable Container

```
public class PlaceBidClient {
    public static void main(String[] args) throws Exception {

        EJBContainer container =
            EJBContainerFactory.createEJBContainer();

        Context context = container.getContext();

        Hello h = (Hello)
            context.lookup("java:global/app/foo/HelloEJB");

        h.sayHello;

        container.close();
    }
}
```

Timer Service

- Programmatic and Calendar based scheduling
 - « Last day of the month »
 - « Every five minutes on Monday and Friday »
- Cron-like syntax
 - second [0..59], minute[0..59], hour[0..23], year
 - DayOfMonth[1..31]
 - dayOfWeek[0..7] or [sun, mon, tue..]
 - Month[0..12] or [jan,feb..]


Timer Service

```
@Stateless
public class WakeUpBean {

    @Schedule(dayOfWeek="Mon-Fri", hour="9")
    void wakeUp() {
        ...
    }
}
```

- EJB Lite + Timer + Asynch calls + Embeddable Container = Batch processing

JPA 2.0



JPA 2.0

- Java Persistent API
- Evolves separately from EJB now
 - JSR 317
- Can also be used in Java SE
- More mappings
 - JoinTable for OneToOne relationship
- Criteria API
- Standard properties in persistence.xml
- Simple Cache API

Collection of basic types

```
@Entity
Public class Item {

    @ElementCollection
    private Set<String> tags;
}
```

- Mapped in a separate table

Better Support of Map

```
@Entity
public class Department {
    ...
    @ElementCollection
    public Map<Integer, Employee> employees
    ...
}
```

- Basic types, Objects, Embeddables
- Mapped in a separate table

Locking Enhancement

```
public enum LockModeType {  
    OPTIMISTIC,  
    OPTIMISTIC_FORCE_INCREMENT,  
    PESSIMISTIC,  
    PESSIMISTIC_FORCE_INCREMENT,  
    NONE  
}
```

- JPA 1.0 only support optimist locking
- Now Pessimist locking
- Multiple places to specify lock
 - Lock, read and lock, read then lock

Criteria API

- Used to define dynamic queries
- Like JPQL, Criteria API is based on Entities
- Allow the construction of an object-based graph
- QueryBuilder Interface

Criteria API

```
QueryBuilder qb = ...
DomainObject o = qb.createQueryDefinition(Order.class);

o.select(o)
.where(o.get("quantity").greaterThan("12"))
.and(o.get("customer").get("surname").equal("Smith"))
.and(o.get("customer").get("name").equal("John")));

// Equivalent query in JPQL

SELECT o
FROM Order o
WHERE o.quantity > 12
      AND o.customer.surname = 'Smith'
      AND o.customer.name = 'John'
```

JAX-RS 1.1

New

Servlet 3.0

JSP 2.2

JSF 2.0

Presentation Tier

EJB 3.1

JTA 1.1

Business Logic Tier

JPA 2.0

Persistence Tier

Java EE 6

Interoperability Tier

JAX-WS 2.2

JAX-RS 1.1

JMS 1.1

WebBeans 1.0

JAX-RS 1.1

- RESTful Services
- POJO and Annotations Based
- Data and functionality are considered resources
- Map HTTP

HTTP	Action	HTTP	Action
GET	Get a resource	PUT	Create or update
POST	Create a resource	Delete	Deletes a resource

- JAX-RS 1.0 has been released

Hello World

```
@Path("/helloworld")
public class HelloWorldResource {

    @GET
    @Produces("text/plain")
    public String sayHello() {
        return "Hello World";
    }
}
```

- <http://example.com/helloworld>

Hello World

Request

```
GET /helloworld HTTP/1.1
Host: example.com
Accept: text/plain
```

Response

```
HTTP/1.1 200 OK
Date: Wed, 12 Nov 2008 16:41:58 GMT
Server: Apache/1.3.6
Content-Type: text/plain; charset=UTF-8
Hello World
```

MIME Types

```
@Path("/helloworld")
public class HelloWorldResource {

    @GET @Produces("image/jpeg")
    public byte[] paintHello() {
        ...
    }

    @POST @Consumes("text/xml")
    public void updateHello(String xml) {
        ...
    }
}
```



Parameters

```
@Path("/users/{userId}")
public class UserResource {


    @GET
    @Produces("text/xml")
    public String getUser(@PathParam("userId")
                          String userName) {
        ...
    }
}
```

- <http://example.com/users/Smith123>

Summary



From simple web application



...to richer ones

**ear in
a cluster**

Presentation Tier

Servlet 3.0

JSF 2.0

Interoperability Tier

JAX-WS 2.2

JAX-RS 1.1

Business Logic Tier

EJB 3.1

JTA 1.1

JMS 1.1

Persistence Tier

JPA 2.0

WebBeans 1.0

Java EE 6

Reference Implementations

- All these specs have reference implementations
 - GlassFish V3 : EJB 3.1 and Servlet 3.0
 - EclipseLink : Java Persistence API (JPA 2.0)
 - Jersey : RESTful web services (JAX-RS 1.0)
 - Metro : Web Services (JAX-WS 2.2)
 - JBoss Seam : Web Beans 1.0
 - Mojarra : JSF 2.0
- And they are production ready

Summary

- Java EE 6 is
 - Simpler (POJO, annotation, less XML, Pruning)
 - Richer (more specifications)
 - Modular (profiles)
 - Standard (no vendor locking)
 - Robust (10th anniversary)

« Forget the past, look to the future, Java EE 6 is the place to go... » - Antonio Goncalves



Questions / Réponses

www.parisjug.org



Copyright © 2008 ParisJug. Licence CC – Creative Commons 2.0 France – Paternité – Pas d'Utilisation Commerciale – Partage des Conditions Initiales à l'Identique



Merci de votre attention!



www.parisjug.org



Licence



Paternité-Pas d'Utilisation Commerciale-Partage des Conditions Initiales à l'Identique
2.0 France

<http://creativecommons.org/licenses/by-nc-sa/2.0/fr/>